

LAGUNA GAS KILNS

GAS-FIRED POTTERY KILNS



The following features are standard on Laguna gas kilns:

- Structural steel frame • 16 gauge steel skin (painted) • Heavy-duty, adjustable-hinge door (specify left or right mounted) (guillotine door optional) • Gasketed, heat-lock door • K-26 firebrick floor • K-23 firebrick walls, arch and door (brick models only; K-26 optional) • 6" pre-compressed, high-purity, fiber panels (fiber models only) • High efficiency, natural draft, ceramic-tip, venturi burners (specify natural gas or propane) • Heavy-duty burner manifold system • Direct-spark, electronic ignition system • Digital high-limit/safety shut-off controller • Manual burner control valves • Water column pressure gauge • Cordite sight tube(s) with peephole plug(s)

The following features are optional on Laguna gas kilns:

- K-26 firebrick walls, arch and door - Recommended for Cone 10 firing - see following page for pricing.
- Programmable controller - 8 programs, 16 segments each (combinable) - \$3,150.00
- Guillotine Door - \$575 • Wind apron (detachable) - \$175.00 • Forced-air burner system - call for quote.
- Hood - galvanized or stainless.

All Items This Page Plus Freight

Standard Model Gas Kilns

Model No. (1)	Stacking Volume (CU. FT.)	Interior Volume (CU. FT.)	Stacking Area (W x D x H)	BTU (per hour)	Burner Qty	Price	K-26Brick Upgrade Package(2)
LE-200-4	4.4	7.9	16" x 16" x 29.6"	164,000	4	\$4,510.00	\$188.00
LE-200-9	9.7	16.4	22" x 22" x 34.6"	195,000	4	\$7,425.00	\$360.00
LE-200-12	12.5	19.5	24" x 24" x 37.2"	95,000	6	\$9,180.00	\$455.00
LE-200-18	18.2	26.2	28" x 28" x 40.1"	262,000	6	\$11,125.00	\$585.00
LE-200-24	25.3	36.0	32" x 32" x 42.75"	360,000	8	\$14,150.00	\$717.00
LE-200-404	41.6	58.5	36" x 36" x 55.5"	585,000	10	\$18,600.00	\$1,190.00
LE-200-24C5	25.3	36.0	32" x 32" x 42.75"	360,000	8	\$16,250.00	\$734.00
LE-200-4C (4/5)	41.6	58.5	36" x 36" x 55.5"	585,000	10	\$20,950.00	\$1,190.00

**** Call for Pricing on Hoods

In addition to the kilns offered above, other sizes and types of kilns are also available. Contact us to discuss the gas kiln most suited to your firing needs. Two K-26 floors and K-23 walls, arches and doors are standard in Laguna gas kilns. For kilns fired to Cone 10 we recommend upgrading to K-26 brick throughout. For downdraft models, add \$75 to listed upgrade package. Optional hood of 14 gauge galvanized steel may be kiln-mounted or suspended from overhead. Stipulate when ordering. Also available in stainless steel for longer life.

"C" designates single-car kiln.

•The minimum gas pressure to fire a Laguna Gas Kiln is 6" WC. A water column gauge is installed on all kilns.

•If firing with LP gas, inquire about the proper regulator for your application.

Furniture kits are optional and are designed to accommodate a variety of ware sizes. Kits assume high-fire application and are manufactured from a high-refractory mullite/cordite clay body. Call for quote on silicon carbide or other high-end refractory products.